

Storm Slimline 3mm Wall Mounted Waterfall Showerhead 500mm x 250mm



Product features:

- Metal construction throughout
- · Minimalist planate design form
- · Single spray pattern showerhead
- · Rub clean anti limescale spray nozzles
- Externally wall fixed for easier installation

Packaged properties:


Box length (mm): 520 Box depth(mm): 60
Box width(mm): 260 Boxed weight (Kg): 3.5

Includes pop up waste?: No Additional comments:

100 Nozzles, includes mesh filter washers

12 litre limiter included

Product dimensions:



Product mounted where: Wall
 Recommended hole size: n/a mm


Overall Height / projection: 43 mm
Exit reach: 375 mm
Exit height: 42 mm
Base size: 160 X 43 mm

• Inlet centre distance(s): 100 mm

• Min. fitting depth required: 60 mm

Max. surface depth:

Product flow characteristics:



- Min / Max water pressure (bar): 0.40* / 5.50
- Part G max. mixed flow rate at 3 bar (I/m): 17.95
- Inlet connection type / length: Semi rigid flexi / 180 mm
 Inlet (plumbing connection) / outlet size: 1/2" F / M10
- Product flow characteristics: N/a
 Non return valve(s) supplied or position: no
- Aerator type: N/a
- Control valve type: N/a (n/a)
 Includes output diverter?: No
- Inlet meshed particle filters included: 0.6 (1/2" gasket)
- Shower hose type / length: N/A / N/A

Warranty Summary (full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
 Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year

Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives