

# Thermostatic Deck Mounted 4 Hole Bath Mixer & Sliding Rail Kit



## Product features:


- Metal & ABS construction
- Thermostatic valve for safety & comfort
- Supplied compete with flexible tail pipes for fast simple fitting
- · Part G compliant for thermostatic bath fillers
- Factory set maximum output temperature 46°C (adjustable)

Packaged properties:

Box length (mm): 800 Box depth(mm): 475
Box width(mm): 255 Boxed weight (Kg): 6.4

Includes pop up waste?: No Additional comments:

## **Product dimensions:**



• Product mounted where: Deck/Wall

• Recommended hole size: 34-40, 22-32, 34-40, 22-32

• Overall Height / projection:

• Exit reach: 213 mm • Exit height: 161 mm • Base size: 107 mm


60, 60, 60, 60 mm

• Inlet centre distance(s):

100, 120, 120 mm

• Min. fitting depth required: n/a mm • Max. surface depth: 30 mm

## **Product flow characteristics:**



- Min / Max water pressure (bar): 0.60\* / 5.50
   \*Detailed minimum pressure requirements for this product: Bath 0.6, Shower 0.5 (bar)
- Part G max. mixed flow rate at 3 bar (I/m): 20.5
- Inlet connection type / length: Flexi / 500 mm
- Inlet (plumbing connection) / outlet size: 1/2" M & 3/4" M / 1/2" M & 3/4" M
- Product flow characteristics: Single Flow Non return valve(s) supplied or position: H&C Inlet
- Aerator type: Flow Straightener
- Control valve type: Thermostatic & 180° Divertor ()
- Includes output diverter?: Yes
- Inlet meshed particle filters included: 0.60 mm

## Warranty Summary (full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year O-rings, hoses & gaskets warranted for 1 year

## Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives