obode

		Product features:	
		Metal construction throughout	
		 Subtle soft sweeping design forn 	n
		• Antisplash spout supplied as sta	ndard
Packaged properties: Box length (mm): 200 Box width(mm): 230	Box depth(mm): 110 Boxed weight (Kg): 2.0	Includes pop up waste?: No Additional comments:	
Product dimensions:			
30	0-50	 Product mounted where: Recommended hole size: 	Wall 52x52 mm
72	200	 Overall Height / projection: Exit reach: Exit height: Base size: Inlet centre distance(s): 	215 mm 200 mm 58 mm 72 mm N/A mm
Chao Bath Spout Wall Mounted	AB4045 v1 (c) alkole tome products the max and the max	 Min. fitting depth required: Max. surface depth: 	30-50 mm N/A mm
Product flow characte	ristics:	• Min / Max water pressure (bar): 0.75	* / 5.50
Flew performance for mode	± AB4045 - Cheo Belh Spout Well Moueted	Part G max. mixed flow rate at 3 bar	(l/m): 19.41
 Inlet connection type / length: Fixed / n/a mm Inlet (plumbing connection) / outlet size: 1/2"M / n/a Product flow characteristics: Single flow 			
		 Product flow characteristics: Single flow Non return valve(s) supplied or position: no 	
s	· · · · · · · · · · · · · · · · · · ·	• Aerator type: Neoperl honeycomb, ca	che (grey)
P-dysamic pressure (bar)		 Control valve type: N/A (N/A) Includes output diverter?: N/A 	
obode the raised of the second	9 data, ni k in specia anti-devia pre pandante No el halta, eksternene for rijetta erver specialista villeri plor note, tile. For olas semaklag in 1902	 Inlet meshed particle filters included Shower hose type / length: N/A / N/A 	
 Warranty Summary (full details a Materials and workmanship Valves and working parts wa Surface warranty defects wa O-rings, hoses & gaskets wa 	defects warranted for 5 years•Clearranted for 5 years•Rearranted for 1 year•Aftarranted for 1 year•Re	structions: ean the mixers and showers regularly as required, using gular cleaning will prevent the build up of lime scale and ter cleaning rinse thoroughly with clean water to remove esidues of liquid soaps, shampoos and shower foams can ater after using, avoid contact with any abrasives	l dirt any cleaner residue