


Product features:

- Luscious European quality chromium plate finish
- Supplied with fixed 3/4" inlets for maximum stability and flow
- · Modern minimalism with flair
- Quarter turn handle action for precise flow control
- Metal & ABS construction

Packaged properties:

Box length (mm): 250 Box depth(mm): 190 Box width(mm): 180 Boxed weight (Kg): 2.4 Includes pop up waste?: No **Additional comments:**

Product dimensions:




• Product mounted where: Surface • Recommended hole size: 30-35 mm

 Overall Height / projection: 139 mm • Exit reach: 110 mm • Exit height: 75 mm · Base size: 45 mm

• Inlet centre distance(s): 180 mm

· Min. fitting depth required: N/A mm · Max. surface depth: 23 mm

Product flow characteristics:



- Min / Max water pressure (bar): 0.70* / 5.00 *Detailed minimum pressure requirements for this product: Bath 0.7, Shower 0.7 (bar)
- Part G max. mixed flow rate at 3 bar (I/m): bath=18.3, shower=14
- Inlet connection type / length: Fixed / 44 mm • Inlet (plumbing connection) / outlet size: 3/4" M /
- Product flow characteristics: Single flow Non return valve(s) supplied or position: no
- Aerator type: Flow straightener
- Control valve type: 3/4" QT CD (3/4 X 46.5 X24)
- Includes output diverter?: Yes
- Inlet meshed particle filters included:
- Shower hose type / length: Smoothflex / 1.50 m

Warranty Summary (full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives