



## 2 handle / 2 exit thermostatic concealed shower




#### Product features:

- · Metal construction throughout
- · Thermostatic valve for safety & comfort
- 2 exit alternate control for output to 2 x shower or 1 x shower & 1 x bath
- Freshly designed contemporary blend
- 5 year limited warranty

Packaged properties:

Box length (mm): 355 Box depth(mm): 150 Box width(mm): 205 Boxed weight (Kg): 3.7 Includes pop up waste?: No **Additional comments:** 

### **Product dimensions:**



 Product mounted where: Wall

• Recommended hole size: 200 x 180 mm


• Overall Height / projection: 63 (max) mm • Exit reach: N/A mm • Exit height: N/A mm · Base size: 155 x 234 mm

• Inlet centre distance(s):

• Min. fitting depth required: 72-78 mm10 mm

· Max. surface depth:

# **Product flow characteristics:**



- Min / Max water pressure (bar): 0.50\* / 5.00 \*Detailed minimum pressure requirements for this product: Shower 0.5, Bath 0.9 (bar)
- Part G max. mixed flow rate at 3 bar (I/m): 17.92

• Inlet connection type / length: Fixed / n/a mm

• Inlet (plumbing connection) / outlet size: 1/2" F / 1/2" F

• Product flow characteristics: N/a

Non return valve(s) supplied or position: h&c inlets

• Aerator type: N/a

• Control valve type: Thermostatic and diverter (8-20)

• Includes output diverter?: Yes

• Inlet meshed particle filters included: 0.60 mm

Shower hose type / length: N/A / N/A

## Warranty Summary (full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years

#### Surface warranty defects warranted for 1 year O-rings, hoses & gaskets warranted for 1 year

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build-up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives