

Ignus single lever

Product code: AT1104 Product Finish: Stainless steel EAN13 barcode: 5060048380842




Product features:

- 304 grade brushed stainless steel construction
- · Single lever control for effortless single handed control
- Solid and functional European architect design styling
- · Antisplash spout supplied as standard
- · Supplied compete with flexible tail pipes for fast simple fitting

Additional information / Parts included:

Note: the image shown may not reflect the product finish, chrome finish is typically depicted

Product dimensions:



- Overall Height / projection: 300 mm
- Exit reach: 186 mm • Exit height: 220 mm Centre distance(s):
- Base diameter(s): 50 mm
- Recommended hole diameter: Ø 35 mm
- Max. surface depth: 40 mm
- Spout diameter: 25 mm Spout aerator size: 18m


Packaged properties:

Box length: 420mm Box depth: 75mm

Box width: 240mm Units per outer: 5

Tap only weight: 1.35kg Boxed weight: 2.12kg

Product flow characteristics:



- Min / Max water pressure: 0.50 / 5.5 bar
- Recommended / Max water temperature: 46°C / 70°C
- Part G Mixed flow rate at 3 bar (litres / min): 09.80
- Control valve type: Single lever ceramic cartridge
- Product flow characteristics: Single flow
- Non return valve(s): Hot & cold (separate)
- Aerator type: Metal fine mesh diffuser
- · Accepts revolve / spray areator: No
- · Spout connection method: N/a
- Tail pipe inlet / outlet size: M10 / 1/2" BSP Female

Materials and workmanship defects warranted for 5 years

• Inlet pipe type / length: flexible stainless braided hose / 400 mm

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of sink & worktop cleaners can also cause damage, so rinse with clean water after using, avoid contact with any abrasives
- Warranty Summary (Full details available on request) Valves and working parts warranted for 5 years Surface warranty defects warranted for 1 year
 - O-rings, hoses & gaskets warranted for 1 year