

Product Finish: Chrome

Product code: AT1122  
EAN13 barcode: 5060048381382




Note: the image shown may not reflect the product finish, chrome finish is typically depicted.

## Product features:

- Metal construction throughout
- Innovative push & pull lateral valve design
- Crisp modernist design lines
- Antisplash spout supplied as standard
- Supplied complete with flexible tail pipes for fast simple fitting

## Additional information / Parts included:

## Product dimensions:




- Overall Height / projection: 382 mm
- Exit reach: 225 mm
- Exit height: 235 mm
- Centre distance(s):
- Base diameter(s): 55 mm
- Recommended hole diameter: Ø 35 mm
- Max. surface depth: 70 mm
- Spout diameter: 24 mm
- Spout aerator size: 22f

## Packaged properties:

Box length: 430mm      Box depth: 70mm  
Box width: 340mm      Units per outer: 5  
Tap only weight: 1.40kg      Boxed weight: 2.15kg

## Product flow characteristics:



- Min / Max water pressure: 0.40 / 5.5 bar
- Recommended / Max water temperature: 46°C / 70°C
- Part G - Mixed flow rate at 3 bar (litres / min): 17.40

- Control valve type: Ceramic disc - slide operation
- Product flow characteristics: Single flow
- Non return valve(s): Hot & cold (integral to tails)

- Aerator type: Plastic mesh diffuser
- Accepts revolve / spray areator: Yes
- Spout connection method: Grub screw

- Tail pipe inlet / outlet size: M12 / 1/2" BSP Male
- Inlet pipe type / length: flexible stainless braided hose / 270 mm

## Care instructions summary:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of sink & worktop cleaners can also cause damage, so rinse with clean water after using, avoid contact with any abrasives

## Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year