# Bayenne Monobloc

Product Finish: Chrome Product code: AT3024

**EAN13 barcode:** 5060048383331



• Quarter turn handle action for precise flow control

• French provincial design aesthetic

• Antisplash spout supplied as standard

• 5 year limited warranty


## Additional information / Parts included:

Triangular stabiliser

Packaged properties:

Box length (mm): 605 Box depth (mm): 85 Tap only weight (kg): 3.00 Box width (mm): 320 Units per outer: 5 Boxed weight (kg): 3.96

## **Product dimensions:**



• Overall Height / projection (mm): 322

Exit reach (mm): 230
Exit height (mm): 229
Centre distance(s): N/A


• Base diameter(s) (mm): 58

• Recommended hole diameter (mm): Ø 35

• Max. surface depth (mm): 60

Spout diameter (mm): 20
Spout aerator size: M24

### **Product flow characteristics:**



- Min / Max water pressure (bar): 0.50 / 5.5
- Recommended / Max water temperature:  $46^{\circ}\text{C}$  /  $70^{\circ}\text{C}$
- $\bullet$  Part G Mixed flow rate at 3 bar (litres / min): 14.45
- Control valve type: Ceramic disc QT
  Product flow characteristics: Single flow
- $\bullet$  Non-return/Check valve(s): Integral to H & C inlets
- Aerator type: Neoperl honeycomb light blue
- Accepts revolve / spray areator: No
- Spout connection method: Locking collar
- Tail pipe inlet / outlet size: 1/2" BSP Male / M10
- Inlet pipe type / length (mm): flexible stainless braided hose / 480

#### Care instructions summary:

- Clean the product regularly using a mild washing up liquid, do not use any other cleaners.
  Regular cleaning will prevent the build up of lime scale and dirt
  After cleaning rinse thoroughly with clean water to remove any cleaner residue
- .Atter cleaning rinse thoroughly with clean water to remove any cleaner residue .Residues of sink & worktop cleaners can also cause damage, so rinse with clean water after using, avoid contact with any abrasives

Warranty Summary (Full details available on request):
. Materials and workmanship defects warranted for 5 years
. Valves and working parts warranted for 5 years
. Surface warranty defects warranted for 1 years
. O-rings, hoses & gaskets warranted for 1 years

