


# Metrik 1.5 Bowl & drainer





\*Important, fabricator / installer notes for undermount & flushmount sinks:

The cut out size indicated is aligned with outside edge of the bowl top radius (see example below).



You should confirm with your client if the worksurface cutout is to be cut flush, inside or outside this suggested perimeter shape & size.

If you create the cutout smaller or larger than the indicated size then the fit of the accessories may be affected and should be physically checked.

#### General:

All details are provided in good faith but do not include the tolerances of the material or manufacturing process.

We request that a test cutout is made in scrap timber and checked against the actual sink to be installed before committing to cutting the final worksurface.


Abode can not accept liability for problems or costs incurred by failure to follow this request.

Note: the dimensions on ceramic fireclay products are subject to wider tolerances due to the nature of this natural material and the firing process.


CAD cutout files can be downloaded from www.abodedesigns.co.uk

19/09/2016 - This sheet is a summary of the product information full details are available on request, errors & omissions excepted, details are subject to change without prior notification. www.abodedesigns.co.uk






587







#### Adittional notes:

Overall product size: 1000 x 500 x 234 corner radius 1mm

Taphole(s) detail: 1 x Ø 35mm, precut Compatability with large square taps: No known incompatibilities Wastehole(s) detail (mm): 90 / 90 / N/A (nb. 90mm wastes accept a waste disposal unit) Min. base unit (refers to space required for bowl, tap and overflow only): fits 800mm carcass Min. Recessed fitting width: required (bowl(s), tap and overflow: 587mm \*Worktop cut out size: 980x480 corner radius 10mm, for .DXF cut files please see www.abode.eu Min. & Max worktop depth or clip depth reach range: 25 - 40mm

Fitting temple supplied? No, use cut out instructions as supplied

Dishwasher under drainer? Distance from top of worktop to underside of the drainer 25mm

Bowl 2 size L x W x D (mm): 174 x 391 x 99

Bowl 2 construction: Welded, 1.00mm

Bowl 2 Wastehole diameter (mm): 90

Bowl 2 texture: Brushed stainless

Bowl 2 apx. volume (litres): 6.70

Bowl 2 floor radius (mm): 12

Bowl 2 overflow: N/A

Bowl details: (sizes in mm unless specified otherwise) Bowl 1 (typically main bowl): Bowl 2 (typically  $\frac{1}{2}$  or  $\frac{3}{4}$  bowl):

### Bowl 1 size L x W x D (mm): 350 x 391 x 195 Bowl 1 construction: Welded, 1.00mm Bowl 1 floor radius (mm): 12 Bowl 1 Wastehole diameter (mm): 90 Bowl 1 overflow: Slotted, barcode pattern Bowl 1 texture: Brushed stainless Bowl 1 apx. volume (litres): 20.80

## Bowl 3:

Bowl 3 size L x W x D (mm): N/A x N/A x N/A Bowl 3 construction: N/A, N/Amm Bowl 3 floor radius (mm): N/A Bowl 3 Wastehole diameter (mm): N/A Bowl 3 overflow: N/A Bowl 3 texture: N/A Bowl 3 apx. volume (litres): N/A