
# abode

## Maxim 1.5 Bowl & drainer



Product dimensions and installation information: note:

580

240


340

symbol indicates position of acoustic pad on stainless products.



\*Important, fabricator / installer notes for undermount & flushmount sinks:

The cut out size indicated is aligned with outside edge of the bowl top radius (see example below).



You should confirm with your client if the worksurface cutout is to be cut flush, inside or outside this suggested perimeter shape & size.

If you create the cutout smaller or larger than the indicated size then the fit of the accessories may be affected and should be physically checked.

#### General:


All details are provided in good faith but do not include the tolerances of the material or manufacturing process.

We request that a test cutout is made in scrap timber and checked against the actual sink to be installed before committing to cutting the final worksurface.

Abode can not accept liability for problems or costs incurred by failure to follow this request.

Note: the dimensions on ceramic fireclay products are subject to wider tolerances due to the nature of this natural material and the firing process.

CAD cutout files can be downloaded from www.abodedesigns.co.uk



### Bowl 2 (typically $\frac{1}{2}$ or $\frac{3}{4}$ bowl):

Bowl 1 floor radius (mm): 35 Bowl 1 Wastehole diameter (mm): 90 Bowl 1 overflow: Slotted, barcode pattern Bowl 1 texture: Brushed stainless Bowl 1 apx. volume (litres): 22.40

Bowl 2 size L x W x D (mm): 147 x 296 x 150 Bowl 2 construction: Welded, 0.70mm Bowl 2 floor radius (mm): 15 Bowl 2 Wastehole diameter (mm): 90 Bowl 2 overflow: N/A Bowl 2 texture: Brushed stainless Bowl 2 apx. volume (litres): 6.20

#### Bowl 3:

Bowl 3 size L x W x D (mm): N/A x N/A x N/A Bowl 3 construction: N/A, N/Amm Bowl 3 floor radius (mm): N/A Bowl 3 Wastehole diameter (mm): N/A Bowl 3 overflow: N/A Bowl 3 texture: N/A Bowl 3 apx. volume (litres): N/A