





Product features:


- Metal construction throughout
- Quarter turn handle action for precise flow control
- · Minimalist planate design form
- Supplied with fixed 3/4" inlets for maximum stability and flow
- A modern design classic style

Packaged properties:

Box length (mm): 280 Box depth(mm): 170
Box width(mm): 210 Boxed weight (Kg): 4.6

Includes pop up waste?: No Additional comments:

Product dimensions:




Product mounted where: SurfaceRecommended hole size: 35 mm

Overall Height / projection:
Exit reach:
Exit height:
Base size:
115 mm
96 mm
34 mm
50 mm

• Inlet centre distance(s): 180 mm

• Min. fitting depth required: n/a mm • Max. surface depth: 1/45 mm

Product flow characteristics:



- Min / Max water pressure (bar): 0.50* / 5.50
 *Detailed minimum pressure requirements for this product: Bath 0.5, Shower 0.75 (bar)
- Part G max. mixed flow rate at 3 bar (I/m): 22.18
- Inlet connection type / length: Fixed / 53 mm
- Inlet (plumbing connection) / outlet size: 3/4" M / N/A
- Product flow characteristics: Single Flow Non return valve(s) supplied or position: No
- · Aerator type: Grey flow straightener
- Control valve type: 3/4 QT CD (8-20) • Includes output diverter?: Yes
- Inlet meshed particle filters included: N/A
- Shower hose type / length: Smoothflex / 1.50 m

Warranty Summary (full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year

Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives