







Product features:


- Metal & ABS construction
- Custom designed for lower range pressures
- · Thermostatic valve for safety & comfort
- 5 year limited warranty
- · Minimalist planate design form

Packaged properties:

Box length (mm): 270 Box depth(mm): 155
Box width(mm): 235 Boxed weight (Kg): 3.3

Includes pop up waste?: No Additional comments:

Product dimensions:



• Product mounted where: Wall


• Recommended hole size: 200 x 170 mm

Overall Height / projection:
 Exit reach:
 Exit height:
 Base size:
 53 mm
 N/A mm
 155 x 234 mm

• Inlet centre distance(s): N/A mm

• Min. fitting depth required: 50-64 mm • Max. surface depth: N/A mm

Product flow characteristics:



- Min / Max water pressure (bar): 0.20* / 5.00
- Part G max. mixed flow rate at 3 bar (I/m): 35
- Inlet connection type / length: Fixed / N/A mm
- \bullet Inlet (plumbing connection) / outlet size: 1/2" M / 1/2" M
- Product flow characteristics: N/A

Non return valve(s) supplied or position: h&c inlet

- Aerator type: N/A
- Control valve type: Thermostatic (new plastic type)
- Includes output diverter?: No
- Inlet meshed particle filters included: 0.60 mm
- Shower hose type / length: N/A / N/A

Warranty Summary (full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
 O-rings, hoses & gaskets warranted for 1 year

Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives