

Euphoria

Circlular Wall Mounted Thermostatic Post Shower with 200mm Showerhead, Hose & Shower Handset

Product features:




- · Thermostatic valve for safety & comfort
- · Leading design features requiring high pressure
- 1/4 turn lock on divertor to handheld showerhead
- · Rub clean anti limescale spray nozzles

Packaged properties:

Box length: 940 mm Box depth: 115 mm Box width: 550 mm Boxed weight: 5.88 kg Includes pop up waste?: No Additional comments:

Product dimensions:




• Overall Height / projection: 1034 mm

• Exit reach: 335 ± 10 mm • Exit height: 914 mm • Centre distance(s): 45 mm

• Base diameter(s): 59 x 38 mm • Product mounted where: Wall · Recommended hole diameter: • Min. fitting depth required: 50 mm

• Max. surface depth:

Product flow characteristics:



• Min / Max water pressure: 1.25 / 5 bar • Part G mixed flow rate at 3 bar (I/m): 16.7

• Max water temperature: 70° C Product flow characteristics:

Aerator type:

• Includes output diverter?: N/A • Control valve type: Thermostatic ()

• Non return valve position: h&c inlet & shower output

• Mesh particle filter size: 0.60 mm

• Inlet / outlet size: 1/2" M / • Inlet type / length: Fixed / mm

Shower hose type / length: N/A / N/A

Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year

Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives