

Serenitie Thermostatic Deck Mounted 3 Hole Bath Mixer & Wall Mounted Shower

	Inermostatic	Deck Mounted 3 Hole Bath Mixer	& wail wounted Showe	
		Product features:		
K II		Metal construction throughout		
		Thermostatic valve for safety & comfort		
_		Supplied compete with flexible tail pipes for fast simple fitting		
		Part G compliant for thermostation	Part G compliant for thermostatic bath fillers	
		• Factory set maximum output temperature 46°C (adjustable)		
Ĩ				
Packaged properties:		Includes pop up waste?: No		
Box length (mm): 440	Box depth(mm): 395	Additional comments:		
Box width(mm): 255	Boxed weight (Kg): 6.5			
Product dimensions:	420	<ul> <li>Product mounted where:</li> <li>Recommended hole size:</li> </ul>	Deck/Wall 34-40, 22-32, 34-40 mm	
1/5,	370	Overall Height / projection:	213 mm	
100 (min)	120 (min) 161	• Exit reach: • Exit height:	161 mm 107 mm	
		Base size:	60, 60, 60 mm	
Tempeau Serenitie Thermosta Dack Mounted 3TH Bath Mixer & Wall Mounted Shower	The second secon	• Min. fitting depth required: • Max. surface depth:	n/a mm 30 mm	
Product flow character	tatic Deck Mounted 3 Hole Dath More: & Wall Mounted Shower	Min / Max water pressure (bar): 0.60     *Detailed minimum pressure requirements for this		
		Part G max. mixed flow rate at 3 bar	<b>· (l/m):</b> 20.5	
20 30 31 31 31 31 31 31 31 31 31 31	a second s	<ul> <li>Inlet connection type / length: Flexi / 500 mm</li> <li>Inlet (plumbing connection) / outlet size: 1/2" M &amp; 3/4" M / 1/2" M &amp; 3/4" M</li> </ul>		
	D75 1 15 2 25 3 4	<ul> <li>Product flow characteristics: Single Non return valve(s) supplied or posit</li> </ul>		
P; dyr	iamic pressure (bar) y vary depending on spoul and shower design	Aerator type: Flow Straightener		
book 2	9 shola, od to le reportional effect prior primate e ul fability, dioale mome the optice entered specification relation prior radios, Min. Phon radio accounting to MINE	<ul> <li>Control valve type: Thermostatic &amp; 1</li> <li>Includes output diverter?: Yes</li> </ul>	80° Divertor ()	
		Inlet meshed particle filters include	<b>d:</b> 0.60 mm	
<ul> <li>Warranty Summary (full details and Materials and workmanship of Valves and working parts wa</li> <li>Surface warranty defects wa</li> <li>O-rings, hoses &amp; gaskets wa</li> </ul>	defects warranted for 5 years • C rranted for 5 years • F arranted for 1 year • A rranted for 1 year • F	nstructions: Clean the mixers and showers regularly as required, using Regular cleaning will prevent the build up of lime scale and After cleaning rinse thoroughly with clean water to remove Residues of liquid soaps, shampoos and shower foams ca vater after using, avoid contact with any abrasives	d dirt any cleaner residue	