



Product features:

- Metal & ABS construction
- Thermostatic valve for safety & comfort
- Supplied complete with flexible tail pipes for fast simple fitting
- Part G compliant for thermostatic bath fillers
- Factory set maximum output temperature 46°C (adjustable)

Packaged properties:

Box length (mm): 445	Box depth(mm): 370
Box width(mm): 360	Boxed weight (Kg): 7.0

Includes pop up waste?: No

Additional comments:

Product dimensions:

Note: Centre distance shown are typical and should be adjusted up or down depending on bath design, overflow position and spout/order of the temperate. We recommend consulting the top hole centres according to your bath design before ordering.

Hose 1250 Max.

Product mounted where:	Deck/Wall
Recommended hole size:	34-40, 50-55, 34-40 mm
Overall Height / projection:	27 mm
Exit reach:	N/A mm
Exit height:	N/A mm
Base size:	60, 60, 85 mm
Inlet centre distance(s):	180, 180 mm
Min. fitting depth required:	n/a mm
Max. surface depth:	30 mm

Tempeau Harmonie Thermostatic 2 Hole Bath Overflow Filler Kit & Wall Mounted Shower

AB3081 v1

(c) abode home products ltd www.abode.co.uk

our policy is to continually improve our products, and accordingly we reserve the right to amend specifications without prior notice.

Product flow characteristics:

Flow performance for model: Tempeau - Thermostatic Deck Mounted 2 Hole Bath Overflow Filler Kit & Wall Mounted Shower

Q: flow rate (l/min)

P: dynamic pressure (bar)

Legend:
 - Hot water
 - Cold water
 - Mixed water (50°C)
 - Showerhead flow
 - Other jets (see 1)
 - Other jets (see 2)
 - Bath fill, hot flow
 - Shower fill, hot flow
 - Vanity Basin fill, hot flow

Min / Max water pressure (bar): 0.75* / 5.50
*Detailed minimum pressure requirements for this product: Bath 0.75, Shower 0.6 (bar)
Part G max. mixed flow rate at 3 bar (l/m): 19
Inlet connection type / length: Flexi / 500 mm
Inlet (plumbing connection) / outlet size: 1/2" M & 3/4" M / 1/2" M & 3/4" M
Product flow characteristics: Single Flow
Non return valve(s) supplied or position: H&C Inlet
Aerator type: Flow Straightener
Control valve type: Thermostatic & 180° Divertor ()
Includes output diverter?: Yes
Inlet meshed particle filters included: 0.60 mm

note 1: Tested using typical spout and shower design. flow may vary depending on spout and shower design

note 2:

abode

© abode, not to be reproduced without prior permission

*Flow rate data shown is correct at the time of testing, abode reserves the right to amend specifications without prior notice. Min. Flow rates according to H&C

<p>Warranty Summary (full details available on request):</p> <ul style="list-style-type: none"> • Materials and workmanship defects warranted for 5 years • Valves and working parts warranted for 5 years • Surface warranty defects warranted for 1 year • O-rings, hoses & gaskets warranted for 1 year 	<p>Care instructions:</p> <ul style="list-style-type: none"> • Clean the mixers and showers regularly as required, using soap, do not use any other cleaners. • Regular cleaning will prevent the build up of lime scale and dirt • After cleaning rinse thoroughly with clean water to remove any cleaner residue • Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives
---	--