

Thermostatic Deck Mounted Bath Overflow Filler Kit with Handshower & Wall Mounted Shower

**Product features:**  Metal & ABS construction 28.915 Thermostatic valve for safety & comfort Supplied compete with flexible tail pipes for fast simple fitting Part G compliant for thermostatic bath fillers • Factory set maximum output temperature 46°C (adjustable) Packaged properties: Includes pop up waste?: No Box length (mm): 445 Box depth(mm): 370 Additional comments: Box width(mm): 360 Boxed weight (Kg): 9.1 Product dimensions: Product mounted where: Deck/Wall Recommended hole size: 34-40, 50-55, 34-40, 34-40, 42-44 mm Overall Height / projection: • Exit reach: 27 mm • Exit height: N/A mm Base size: N/A mm 60, 60, 60, 40, 85 mm Inlet centre distance(s): 180, 180, 110, 120 mm • Min. fitting depth required: n/a mm • Max. surface depth: 30 mm abode Product flow characteristics: • Min / Max water pressure (bar): 0.60\* / 5.50 \*Detailed minimum pressure requirements for this product: Bath 0.6, Shower 0.6 (bar) e for model: Tempeau - Thermostatic Deck Mounted Bath Overflow Filler Kit with Handshower & Wall Mounted Sho • Part G max. mixed flow rate at 3 bar (I/m): 22.8 • Inlet connection type / length: Flexi / 500 mm • Inlet (plumbing connection) / outlet size: 1/2" M & 3/4" M / 1/2" M & fown 15 3/4" M 10 تستهلتان شتا المسترمشية لتدي · Product flow characteristics: Single Flow Non return valve(s) supplied or position: H&C Inlet 0.2 0.3 0.4 0.5 0.75 15 Aerator type: Flow Straightener note 1: note 2: Handshower Trested using typical spout and shower design, flow may vary depending on spout and shower design • Control valve type: Thermostatic, 3/4 QT CD & 180° Divertor () obode Includes output diverter?: Yes · Inlet meshed particle filters included: 0.60 mm Warranty Summary (full details available on request): Care instructions: Materials and workmanship defects warranted for 5 years Clean the mixers and showers regularly as required, using soap, do not use any other cleaners. Regular cleaning will prevent the build up of lime scale and dirt Valves and working parts warranted for 5 years

- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives