


Extase Thermostatic Deck Mounted Bath Overflow Filler Kit with Handshower & Wall Mounted Shower

Product features: Metal & ABS construction Thermostatic valve for safety & comfort Supplied compete with flexible tail pipes for fast simple fitting • Part G compliant for thermostatic bath fillers • Factory set maximum output temperature 46°C (adjustable) Packaged properties: Includes pop up waste?: No Box length (mm): 445 Box depth(mm): 370 Additional comments: Box width(mm): 360 Boxed weight (Kg): 9.5 Product dimensions: Product mounted where: Deck/Wall Recommended hole size: 34-40, 50-55, 34-40, 34-40, 42-44 mm Overall Height / projection: • Exit reach: 27 mm • Exit height: N/A mm Base size: N/A mm 50, 50, 50, 50 85 mm • Inlet centre distance(s): 180, 180, 110, 120 mm • Min. fitting depth required: n/a mm • Max. surface depth: 30 mm abode and accord right to

Product flow characteris



roduct flow characteristics:	• Min / Max water pressure (bar): 0.60* / 5.50 *Detailed minimum pressure requirements for this product: Bath 0.6, Shower 0.6 (bar)
Flow performance for model: Tempeau - Thermostatic Deck Mounted Bath Overflow Filler Kit with Handshower & Wall Mounted Bhover 30 21 25 25 25 25 25 25 25 25 25 25 25 25 25	Part G max. mixed flow rate at 3 bar (I/m): 22.8
	 Inlet connection type / length: Flexi / 500 mm Inlet (plumbing connection) / outlet size: 1/2" M & 3/4" M / 1/2" M & 3/4" M
	 Product flow characteristics: Single Flow Non return valve(s) supplied or position: H&C Inlet
01 02 03 0.4 0.5 075 1 16 2 26 3 4 P. dynamic pressure (bit) Total T. Histolatower	Aerator type: Flow Straightener
DOM 2 Traded using typical good and shower design. Object 6 abole, not be a reproduced without prior parmatain Object 6 abole, not be a reproduced without prior parmatain *Prior set table downs usered at the the of bading abole report to each quick show their parmatain without prior parmatain	 Control valve type: Thermostatic, 3/4 QT CD & 180° Divertor () Includes output diverter?: Yes
	Inlet meshed particle filters included: 0.60 mm
	instructions:
Materials and workmanship defects warranted for 5 years • Valves and working parts warranted for 5 years •	Clean the mixers and showers regularly as required, using soap, do not use any other cleaners. Regular cleaning will prevent the build up of lime scale and dirt
Surface warranty defects warranted for 1 year	After cleaning rinse thoroughly with clean water to remove any cleaner residue
	Desidues of liquid soons, sharpess and shower forms on slop source demoses as rises with slop

- Surface warranty defects warrant • O-rings, hoses & gaskets warranted for 1 year
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives