


Product features:

- Metal construction throughout
- Single lever control for effortless single handed control
- Supplied compete with flexible tail pipes for fast simple fitting
- · Minimalist planate design form

Packaged properties:

Box length (mm): 420 Box depth(mm): 100 Box width(mm): 180 Boxed weight (Kg): 2.9 Includes pop up waste?: No **Additional comments:**

Product dimensions:




 Product mounted where: Surface • Recommended hole size: 35 mm

 Overall Height / projection: 331 mm • Exit reach: 131 mm • Exit height: 237 mm • Base size: 50 mm

• Inlet centre distance(s): n/a mm

• Min. fitting depth required: N/A mm Max. surface depth: 50 mm

Product flow characteristics:



- Min / Max water pressure (bar): 1.00* / 5.50
- Part G max. mixed flow rate at 3 bar (I/m): 11.18
- Inlet connection type / length: Flexi / 600 mm
- Inlet (plumbing connection) / outlet size: 1/2" F / M8
- Product flow characteristics: Single flow Non return valve(s) supplied or position: No
- Aerator type: Clear plastic anti-splash (flow straightener)
- Control valve type: Single lever (25mm)
- Includes output diverter?: N/A
- Inlet meshed particle filters included: No
- Shower hose type / length: N/A / N/A

Warranty Summary (full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year O-rings, hoses & gaskets warranted for 1 year

Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives