

Product features:

- Metal construction throughout
- Modern minimalism with flair
- Single lever control for effortless single handed control
- Antisplash spout supplied as standard
- Single spray pattern showerhead


Packaged properties:

Box length (mm): 1200	Box depth(mm): 135
Box width(mm): 500	Boxed weight (Kg): 10.0

Includes pop up waste?: No


Additional comments:
Metal showerhead

Product dimensions:



- **Product mounted where:** Floor
- **Recommended hole size:** N/A mm
- **Overall Height / projection:** 1089 mm
- **Exit reach:** 240 mm
- **Exit height:** 798 mm
- **Base size:** 97 mm
- **Inlet centre distance(s):** N/A mm
- **Min. fitting depth required:** 50 mm
- **Max. surface depth:** N/A mm

Product flow characteristics:



- **Min / Max water pressure (bar):** 1.50* / 5.50
*Detailed minimum pressure requirements for this product: Bath 1.5, Shower 1.5 (bar)
- **Part G max. mixed flow rate at 3 bar (l/m):** 13.91
- **Inlet connection type / length:** Fixed / N/A mm
- **Inlet (plumbing connection) / outlet size:** 1/2" F / N/A
- **Product flow characteristics:** Single flow
- **Non return valve(s) supplied or position:** no
- **Aerator type:** Rectangular Neoperl antisplash (high flow)
- **Control valve type:** Single lever (35mm)
- **Includes output diverter?:** Yes
- **Inlet meshed particle filters included:** N/A
- **Shower hose type / length:** Smoothflex / 1.50 m

Warranty Summary (full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year

Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives