

Product Finish: Stainless steel

Product code: AT1199
EAN13 barcode: 5060048382945



Product features:


- 304 grade brushed stainless steel construction
- Single lever control for effortless single handed control
- Multi spray pattern showerhead
- Supplied complete with flexible tail pipes for fast simple fitting
- Polished stainless steel spring

Additional information / Parts included:

Includes triangular stabiliser and bracket to screw tap to worktop underside

Note: the image shown may not reflect the product finish, chrome finish is typically depicted.

Product dimensions:



- Overall Height / projection: 670 mm
- Exit reach: 250-500 mm
- Exit height: 210 mm
- Centre distance(s):


- Base diameter(s): 55 mm
- Recommended hole diameter: Ø 35 mm
- Max. surface depth: 50 mm

- Spout diameter: n/a mm
- Spout aerator size: n/a

Packaged properties:

- Box length: 990mm Box depth: 80mm
- Box width: 360mm Units per outer: tbc
- Tap only weight: 3.21kg Boxed weight: 5.11kg

Product flow characteristics:



- Min / Max water pressure: 1.00 / 5.5 bar
- Recommended / Max water temperature: 46°C / 70°C
- Part G - Mixed flow rate at 3 bar (litres / min): 10.12

- Control valve type: Single lever ceramic cartridge
- Product flow characteristics: Single flow
- Non return valve(s): Hot & cold (integral to tails) & sprayhead

- Aerator type: Plastic mesh diffuser /spray
- Accepts revolve / spray areator: No
- Spout connection method: Grub screw

- Tail pipe inlet / outlet size: M10 / 1/2" BSP Male
- Inlet pipe type / length: flexible stainless braided hose / 245 mm

Care instructions summary:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of sink & worktop cleaners can also cause damage, so rinse with clean water after using, avoid contact with any abrasives

Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year