

Product Finish: Chrome

Product code: AT2074
EAN13 barcode: 5060344155960



Product features:


- Supplied complete with flexible tail pipes for fast simple fitting
- Single lever control for effortless single handed control
- Single spray pattern showerhead
- Solid and functional European architect design styling
- Antisplash spout supplied as standard

Additional information / Parts included:

SCO06050 fixing kit
The installation of this product should respect requirement IRN R090.

Note: the image shown may not reflect the product finish, chrome finish is typically depicted.

Product dimensions:



OPHELIA
MONOBLOC V1

abode

(c) abode home products ltd
www.abode.eu
Our design is continually
improved and developed products,
and accordingly we reserve the
right to amend specifications
without prior notice.

- Overall Height / projection: 478 mm
- Exit reach: 195 mm
- Exit height: 163 mm
- Centre distance(s):


- Base diameter(s): 48 mm
- Recommended hole diameter: Ø 35 mm
- Max. surface depth: 50 mm

- Spout diameter: 19 mm
- Spout aerator size: M24F

Packaged properties:

- Box length: 435mm
- Box depth: 70mm
- Box width: 340mm
- Units per outer: 5
- Tap only weight: 1.77kg
- Boxed weight: 2.50kg

Product flow characteristics:



- Min / Max water pressure: 0.75 / 5.50 bar
- Recommended / Max water temperature: 46°C / 70°C
- Part G - Mixed flow rate at 3 bar (litres / min): 11.69

- Control valve type: Single lever ceramic cartridge
- Product flow characteristics: Single flow
- Non return valve(s): Hot & cold (integral to tails), 1 x in spray head

- Aerator type: Honeycomb aerator
- Accepts revolve / spray areator: No
- Spout connection method: Grub screw

- Tail pipe inlet / outlet size: M10 / 1/2" BSP Male
- Inlet pipe type / length: flexible stainless braided hose / 360 mm

Care instructions summary:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build-up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of sink & worktop cleaners can also cause damage, so rinse with clean water after using, avoid contact with any abrasives

Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year