

Product Finish: Stainless steel

Product code: AT2079  
EAN13 barcode: 5060344156080



**Product features:**


- 304 grade brushed stainless steel construction
- Single lever control for effortless single handed control
- Multi spray pattern showerhead
- Supplied complete with flexible tail pipes for fast simple fitting
- Polished stainless steel spring

**Additional information / Parts included:**

Includes Cache key.  
Flow results shown include non return valves (not supplied).

Note: the image shown may not reflect the product finish, chrome finish is typically depicted.

**Product dimensions:**



- Overall Height / projection: 611 mm
- Exit reach: 220 mm
- Exit height: 200 mm
- Centre distance(s):


- Base diameter(s): 51 mm
- Recommended hole diameter: Ø 35 mm
- Max. surface depth: 50 mm

- Spout diameter: n/a mm
- Spout aerator size: M22 x 1 female

**Packaged properties:**

- Box length: 800mm                      Box depth: 85mm
- Box width: 350mm                      Units per outer: tbc
- Tap only weight: 3.49kg                Boxed weight: 4.56kg

**Product flow characteristics:**



- Min / Max water pressure: 1.50 / 5.50 bar
- Recommended / Max water temperature: 46°C / 70°C
- Part G - Mixed flow rate at 3 bar (litres / min): 07.01

- Control valve type: Single lever ceramic cartridge
- Product flow characteristics: Single flow
- Non return valve(s): Included in sprayhead, required on both hot and cold supply (not supplied)

- Aerator type: Honeycomb
- Accepts revolve / spray areator: No
- Spout connection method: Grub screw
- Tail pipe inlet / outlet size: M10 / 1/2" BSP Female

**Care instructions summary:**

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build-up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of sink & worktop cleaners can also cause damage, so rinse with clean water after using, avoid contact with any abrasives

**Warranty Summary** (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year