abode

Theorem 1.5 Bowl & drainer



symbol indicates position of acoustic pad on stainless products. Product dimensions and installation information: note:

170

551

211

255

304-10+11

BOWL(S)

OVERFLOW,

tap area

551

Wastehole(s) detail (mm): 90 / 90 / N/A (nb. 90mm wastes accept a waste disposal unit)

Min. base unit (refers to space required for bowl, tap and overflow only): fits 600mm carcass

Dishwasher under drainer? Distance from top of worktop to underside of the drainer 13mm

*Worktop cut out size: 982x482 corner radius 10mm, for .DXF cut files please see www.abode.eu

R12

40

Bowl 2 (typically $\frac{1}{2}$ or $\frac{3}{4}$ bowl):

Bowl 2 floor radius (mm): 12

Bowl 2 texture: Brushed stainless

Bowl 2 apx. volume (litres): 8.60

Bowl 2 overflow: N/A

Bowl 2 size L x W x D (mm): 170 x 300 x 170

Bowl 2 construction: Pressed, 1.00mm

Bowl 2 Wastehole diameter (mm): 90

13

Œ

1000

R12

INSET CUT OUT

982

Overall product size: 1000 x 500 x 220 corner radius 10mm

Compatability with large square taps: No known incompatibilities

Min. & Max worktop depth or clip depth reach range: 28 - 48mm

Fitting temple supplied? No, use cut out instructions as supplied

Bowl details: (sizes in mm unless specified otherwise)

Min. Recessed fitting width: required (bowl(s), tap and overflow: 551mm

Taphole(s) detail: 1 x Ø 35mm, precut

Bowl 1 (typically main bowl):

Bowl 1 floor radius (mm): 12

Bowl 1 texture: Brushed stainless

Bowl 1 apx. volume (litres): 21.60

Bowl 1 size L x W x D (mm): 340 x 400 x 200

Bowl 1 construction: Pressed, 1.00mm

Bowl 1 Wastehole diameter (mm): 90 Bowl 1 overflow: Slotted, barcode pattern

170

R10


482

R10

Adittional notes:

*Important, fabricator / installer notes for undermount & flushmount sinks:

The cut out size indicated is aligned with outside edge of the bowl top radius (see example below).



You should confirm with your client if the worksurface cutout is to be cut flush, inside or outside this suggested perimeter shape & size.

If you create the cutout smaller or larger than the indicated size then the fit of the accessories may be affected and should be physically checked.

General:

All details are provided in good faith but do not include the tolerances of the material or manufacturing process.

We request that a test cutout is made in scrap timber and checked against the actual sink to be installed before committing to cutting the final worksurface.

Abode can not accept liability for problems or costs incurred by failure to follow this request.

Note: the dimensions on ceramic fireclay products are subject to wider tolerances due to the nature of this natural material and the firing process.

CAD cutout files can be downloaded from www.abodedesigns.co.uk

Bowl 3 size L x W x D (mm): N/A x N/A x N/A

Bowl 3 construction: N/A, N/Amm

Bowl 3 Wastehole diameter (mm): N/A

Bowl 3 floor radius (mm): N/A

Bowl 3 apx. volume (litres): N/A

Bowl 3 overflow: N/A

Bowl 3 texture: N/A

Bowl 3:

